



Lhov.
The shape of
Extraordinary.

Design Fabrizio Crisà

elica



01



All you need is Lhov

elica



Space Reshaper.

All you need is Lhov.

- 3 appliances in one: oven, hob, extractor hood. Everything you need to cook in the space of a kitchen drawer.
- New size: 90 x 36 cm. Perfect integration into standard cabinets.
- Space saving (bottom drawer usability)

Odour Stopper.



- Lhov removes fumes and odors from the hob and from the oven.
- The ventilation system on the hob can be manual or automatic: it recognizes the cooking zones and regulates the extraction
- LHOV captures vapours coming out from the oven at the opening of the door

- | | | | |
|--|---------------------|--|-----------------------|
| | Oven air cleaning | | Selective autocapture |
| | Long life filter ++ | | Brushless |
| | Delay switch off | | Maintenance alarm |

elica

Over the Hob.



5 cooking zones with double bridge and cooking flow.

Automatic functions.

Fast Boiling.


 Cooking flow	 Melting
 Warming	 Simmering
 Fast boiling	 Tasty fry
 Bridge zone	 Stop & go
 Recall	 Timer
 Pot self detection	

elica

Oven Hero.



- Cavity (30% larger than traditional ovens) for cooking dishes side by side and large foods with uniform results.
- Full steam (100% steam) and different steam levels
- Air Frying integrated function
- Selective Grill (Left or Right)
- Food Probe and Automatic Programs



Ultra Wide Cooking


Steam



Food probe



Air frying




Multi Cooking



Automatic Programs



Selective Grill



Sliding guides



Cool door



Soft closing

elica

Smart Control.



- Digital 7 inches touch display
- Easy and intuitive management
- Software update through WiFi
- Power limitation and power management.
- Electronic door opening



Auto Door




Connectivity



Power limitation



Eco clean



Easy to maintain



Child lock

LHOV

The shape of Extraordinary

KITCHEN STUDIOS / DESIGNERS & ARCHITECTS

INNOVATIVE SPACE MANAGEMENT

- INEDITED and COOL SPACE DESIGN
- LINEARITY OF THE KITCHEN is preserved
- PREMIUM PERCEPTION (by TECHNOLOGY and DESIGN) support a higher price point
- SINGLE COOKING UNIT
- FREE UP THE SPACE OF THE HOOD (like asp hobs)
- FREE UP THE COLUMN for forniture or other complements (WINE CELLARS)

INSTALLATORS/ MANUFACTURER

SUPER EASY INSTALLATION

- LHOV INSTALLATION IS EASIER AND FASTER THAN 3 SINGLE APPLIANCES
- SINGLE UNIT DELIVERY

CONSUMERS

- COOL and INNOVATIVE DESIGN SOLUTION for the main COOKING appliances. It OPTIMIZES SPACE preserving A PERFECT INTEGRATION IN THE KITCHEN
- AIR CLEANING: NO MORE ODOUR NOR VAPOUR (FROM HOB AND OVEN)
- NEW COOKING EXPERIENCE provided by:
 - OVEN SHAPE AND DIMENSION
 - THE NEW SHAPE OF COMBI STEAM COOKING
 - HOB ERGONOMY and FLEXIBILITY
 - SMART SOLUTIONS AND AUTOMATIC FUNCTIONS
 - MOBILE-LIKE INTERACTION & CONNECTIVITY
 - EASY CLEANING AND MANTEINANCE

One look is enough to understand: the All-In-One LHOV will change your cooking experience forever. Design, dimensions and performance of the hob, oven and hood combine in a new way to free and express your creativity to the maximum. Allowing everyone, even the less experienced, to try their hand at any preparation and recipe. Without any more worries, with so much satisfaction.

With LHOV, cooking becomes extraordinary.




02



Datasheet

LHOV - Datasheet

HOB

DIMENSION	90 x 56,5
COOKING ZONES	5
LEVELS	9 + B
BRIDGE ZONES	2 bridge
CHILD LOCK	YES
TIMER	Timer / Egg Timer
AUTOMATIC FUNCTIONS	Warming/ Melting, Simmering, Cooking Flow, Automatic heat-up
PAUSE & RECALL	YES
 Cooking Flow	 Melting Mode
 Warming Mode	 Simmering mode
 Fast Boiling	 Tasty Fry
 Bridge Zone	 Stop&Go
 Recall	 Timer
 Pot Self Detection	

VENTILATION

EEI	A+
AIRFLOW	1200 m ³ /h
NOISE	62
LEVELS	100 + 2B
AUTOCAPTURE	YES
SELECTIVE ASPIRATION	LEFT / RIGHT
TIMER	YES
GREASE FILTERS	3d Aluminium
ODOUR FILTERS	Ceramic (high performance Long life)
CAVITY VAPOURS ASPIRATION	YES
 Oven Air Cleaning	 Selective Autocapture
 Long Life Filter ++	 Brushless
 Delay Switch Off	 Maintenance Alarm

AWARDS



CROSS

ABSORPTION POWER LIMITATION 13 KW ANY

 Power Limitation

 Child Lock

 Connectivity


 Easy to Maintain

 Total Integration

 Super Easy Installation

OVEN

TYPE	Combi Steam
DIMENSION	90 x 36
TEMP RANGE (°C)	30 - 280
FOOD PROBE	YES
DOOR	Flush handle – Auto Opening – Soft Closing - Cool door (3 glasses)
LIGHTS	4 spot led
LEVELS	4
GUIDES	Telescopic guides (1 level)
CLEANING	Hydrocleaning with Steam
EEI	A+
CAVITY VOLUME	63 l
ACCESSORIES	1 glass baking tray, 1 wire rack, 1 steam trays set, 1 air frying tray (tbc)



COOKING PROGRAMS (MANUAL)

M	TOP BOTTOM HEAT
U	FAN
L	INTENSIVE
T	GRILL
I	FAN GRILL
S	SLOW COOK
E	BOTTOM HEAT
A	AIR FRY
M	PIZZA
E	BREAD
C	ECO FAN

S	FULL STEAM
T	HIGH STEAM + FAN
E	MID STEAM + FAN
A	MID STEAM
M	LOW STEAM + FAN
E	PIZZA (STEAM)
C	BREAD (STEAM)
I	INTENSIVE (STEAM)

S	DEFROST
P	PLATE WARM
E	KEEP WARM
C	DEHYDRATE
I	DOUGH PROVING
A	REHEAT

DISHES (AUTO PROGRAMS)

CAKES	MUFFINS
	CROISSANTS
	PIES

YOGURT	YOGURT
	BREAD ROLL

BREAD	BAGUETTE
	SAVOURY PIE

PIZZA	PIZZA
	FAMILY PIZZA

PASTA	CANNELLONI
	LASAGNE

MEAT	PASTA BAKE
	LEG OF LAMB

MEAT	ROAST BEEF
	ROAST VEAL

MEAT	FILLET OF BEEF
	ROAST PORK

MEAT	ROAST CHICKEN
	CHICKEN LEG

MEAT	MEAT LOAF
	WHOLE FISH

SIDE DISHES	FISH FILLET
	BAKED POTATOES

SIDE DISHES	ROAST POTATOES
	ROASTED VEGETABLES


OVEN CLEANING, EASY AND EFFECTIVE, thanks to STEAM

Hydrolytic oven cleaning guarantees the best result with minimum effort and energy consumption, using only water and detergent, appropriately managed by the dedicated cycle.

The steam circuit optimizes the process, allowing total cleaning of the oven cavity in a few simple steps. Periodically the product will notify the need to carry out this operation, the user will only have to refill the water tank and activate the desired cleaning cycle (Steam Cleaning or Steam Cleaning Plus for more stubborn dirt), delegating all the rest to LHOV.

elica

LHOV content



WIRE RACK



PERFORATED TRAY
Allows steam to reach the food completely



SHALLOW TRAY
To collect condensation water dripping down



AIR FRYING WIRE RACK
Special pattern for air convection




GLASS TRAY



STEAM COOKING SET
Wire frame supporting the steam trays.




WIRE FRAME SUPPORT




AIR FRYING SET
Wire frame supporting the air frying wire rack



FOOD PROBE



STEAM WATER TANK



ADDITIONAL SUPPORT FOR PIZZA TRAYS

ALL THE COMPONENTS ARE INCLUDED IN THE PACKAGING

Only with Lhov.

ULTRAWIDE COOKING

The cooking space is so large that you can cook a big quantity of food even on a single level, without the inconvenience of managing multiple racks.

CLEAN AIR IN THE OVEN

No more hot air in your face. It is the revolutionary extraction system that captures the air automatically removing vapours and odour from the oven. Thus preventing them from escaping when the door is opened.

AUTOMATIC DOOR

The door without a handle. To manage it, all you need is a light pressure on the display or a simple voice command (very useful if you are holding trays and containers)

SELECTIVE AUTOCAPTURE

The hob recognizes the active cooking zones and sets the extraction only where it is necessary. A great saving further improved by the system which reduces the suction power at the end of cooking , eliminating residual steam.

MULTI COOKING

Manual programs can be combined sequentially. For example, you can bake bread after it has risen or grill lasagna at the end of the cooking. Without any interruptions.

AUTOMATIC PROGRAMS

It allows you to select the type of dish you want to cook, the desired degree of cooking (medium, well done, rare), the quantity of portions, the oven will do everything by itself.

STEAM

This method of cooking enhances the taste and nutritional properties of all the foods: vegetables, meat, fish, bread, etc. All crunchy on the outside and tender on the inside.

AIR FRYING

Finally, you can cook chips, fish, chicken wings , croquettes and fried vegetables by reducing the amount of oil while enhancing flavour and crunchiness.

SELECTIVE GRILL

A function that allows you to differentiate the grilling of different dishes or to use only half the oven to cook dishes side by side while saving energy.

COOKING FLOW

Each zone activates the preset power when it detects the presence of a pan. You can go from boiling lively to keeping a dish warm simply by moving the pan from one cooking zone to another.

03




Installation

elica

LHOV




Main product dimensions



elica

LHOV


Main product dimensions



LHOV

Flexibility in cabinet installation – cut out



The product installation cut-out is realized with the standard process, the same that is used for a standard hob or aspiration hob



ON TOP



FLUSH

CUT OUT




Installation M1 - The profile overlaps and protrudes from the top in the frontal area (Over Front)

STANDARD
PROCESS



Installation M2 - The aesthetic profile is completely in line with the top (Filo Front)

STANDARD PROCESS +
MILLING IN THE FRONT



Installation M3 - The countertop is free and visible in the frontal part (No Front)

STANDARD
PROCESS

LHOV


Flexibility in cabinet installation – cut out

Frontal Profile always matches the thickness of the countertop thanks to the multiple versions available as accessories (Installation M1 and M2)

Profile "only-on-top" is available too (Installation M3)

On top and Flush installations are possible (see at the table for different options according to different thicknesses)

Flush installation is referred to glass layer, the upper metal profile has a thickness of 1,5 mm , which protrudes above the surface of the countertop and glass itself





Frontal Aesthetic profile	on top installation	filo top installation	Countertop thickness
yes	yes	no	12 mm
yes	yes	no	16 mm
yes	yes	no	18 mm
yes	yes	yes	20 mm
yes	yes	yes	25 mm
yes	yes	yes	30 mm
yes	yes	yes	38 mm
yes	yes	yes	40 mm
yes	yes	yes	50 mm
no	yes	yes	> 12 mm

LHOV

Installation M1



The profile overlaps and protrudes from the top in the frontal area



LHOV

Installation M2



The top can be milled in the frontal area to bring the aesthetic profile completely in line with the top



LHOV

Installation M3

The countertop is free and visible in the frontal part



LHOV

Flexibility in cabinet installation – countertop and drawers alignment

Oven is always aligned to the front of the drawers. Specific spacers are provided to compensate according to different thickness of drawers doors

Profile and hob can be aligned with the top projection, sliding forward



Es. 1 - Non-protruding top



Es. 2 - Protruding top, profile and hob moved forward for alignment

elica

LHOV

Flexibility in cabinet installation – different cabinet heights

LHOV is always positioned in the upper part of the cabinet and its installation is adaptable to the different heights of standard kitchen cabinets



Es. 1 - 72 cm base with 36 cm drawers



Es. 2 - 84 cm base unit with 36 cm top drawers
and 48 cm bottom drawers





Es. 3 - 84 cm base with 42 cm top and bottom
drawers and compensation profile under LHOV




LHOV

Flexibility in cabinet installation – exhaust or recycling

- EXHAUST



- RECYCLING



With new curves compliant
also with 6 cm plinth height
(under development)

elica Duct out installation

Lhov può essere installato in versione aspirante grazie alle tubazioni che Elica mette a disposizione (acquistabili separatamente). Queste consentono di uscire direttamente sul retro o di canalizzare i fumi passando sotto allo zoccolo o sotto al pavimento, verso un punto di uscita esterno all'abitazione, assicurando elevate prestazioni e minima rumorosità.

Lhov can be installed in duct-out version thanks to the piping by Elica (to be purchased separately). Piping allows to have a rear outlet or to channel the fumes under the plinth or the floor, towards an exit point located outside the home, ensuring high performance and very low noise levels.



Esempi di installazione (versione aspirante)
Example of installation (duct-out version)



Uscita posteriore
Rear outlet



Uscita laterale
Side outlet

elica Filtering installation

Plinth in

Con questo kit il prodotto può essere installato in modalità filtrante.

L'aria filtrata viene convogliata all'interno della zoccolo e fuoriesce in maniera diffusa grazie all'apertura di sfogo, che può essere rifinita esteticamente con il profilo cromato in dotazione.

With this kit, you can install the appliance in filtering mode.

Filtered air is channelled into the plinth and exits diffusely through the vent opening, which can be finished with a chrome-plated profile.

Kit installazione filtrante sotto zoccolo (min h6cm)

Filtering installation kit under plinth (min h6cm)

KIT0167756

€ 243,00

- Filtri ceramici (2 pezzi)
- Curva rettangolare 90° - 94x227 mm
- Tubo rettangolare 500x94x227 mm
- Curva rettangolare 90° da vert. 94x227 mm a orizz. 55x227 mm
- Deflettore sotto lo zoccolo
- Profilo estetico cromato
- Nastro adesivo

- Ceramic filters (2 pieces)
- 90° - 94x227 mm rectangular bend
- 500x94x227 mm rectangular pipe
- 90° rectangular bend from vert. 94x227 mm to horiz. 55x227 mm
- Under baseboard deflector
- Chrome-plated trim profile
- Adhesive Tape



* per il corretto funzionamento lasciare almeno 5 cm tra uscita e pavimento

* leave at least 5 cm gap between the outlet and the floor to ensure proper operation.

elica Filtering installation

Plinth in Curve

Con questo kit il prodotto può essere installato in modalità filtrante. L'aria filtrata viene convogliata all'interno della zoccolo e fuoriesce in maniera diffusa grazie all'apertura di sfogo, che può essere rifinita esteticamente con il profilo cromato in dotazione.

With this kit, you can install the appliance in filtering mode. Filtered air is channelled into the plinth and exits diffusely through the vent opening, which can be finished with a chrome-plated profile.

Kit installazione filtrante sotto zoccolo (min h6cm)

Filtering installation kit under plinth (min h6cm)

KIT0167756

€ 243,00

- Filtri ceramici (2 pezzi)
- Curva rettangolare 90° - 94x227 mm
- Tubo rettangolare 500x94x227 mm
- Curva rettangolare 90° da vert. 94x227 mm a orizz. 55x227 mm
- Deflettore sotto lo zoccolo
- Profilo estetico cromato
- Nastro adesivo
- Ceramic filters (2 pieces)
- 90° - 94x227 mm rectangular bend
- 500x94x227 mm rectangular pipe
- 90° rectangular bend from vert. 94x227 mm to horiz. 55x227 mm
- Under baseboard deflector
- Chrome-plated trim profile
- Adhesive Tape



Available from January 2025

Plinth Out

Questo kit permette di convertire e installare il prodotto in modalità filtrante, convogliando l'aria depurata fino a farla uscire dallo zoccolo con l'ausilio di una speciale tubazione a imbuto (che termina con un profilo a rifinitura del foro di sfogo).

By purchasing this kit, it is possible to convert and install the product in filtering mode, thus conveying purified air into, and then outside the baseboard, through a special funnel-shaped pipe with an aesthetic profile on its edge, finishing the vent hole.


Kit installazione filtrante fuori zoccolo (min h6cm)

Filtering installation kit out of the plinth (min h6cm)

KIT0167757

€ 280,00

- Filtri ceramici (2 pezzi)
- Curva rettangolare 90° - 94x227 mm
- Tubo rettangolare 500x94x227 mm
- Curva rettangolare 90° da vert. 94x227 mm a orizz. 50x227 mm
- Raccordo di uscita esterno allo zoccolo completo di profilo cromato
- Tubo rettangolare 218x55x300 mm
- Supporto per raccordo di uscita
- Nastro adesivo
- Ceramic filters (2 pieces)
- 90° - 94x 27 mm rectangular bend
- 500 x 94x227 mm rectangular pipe
- 90° rectangular bend from vert. 94x227 mm to horiz. 50x227 mm
- Outlet connection to be fitted outside the baseboard, provided with chrome-plated trim profile
- 218x55x300 mm rectangular pipe
- Outlet connection support
- Adhesive tape




Available from January 2025


elica

LHOV - INSTALLATION KIT



PLINTH IN



PLINTH IN CURVE




PLINTH OUT



KIT0203143 - KIT PLINTH IN



KIT204095 - KIT PLINTH IN CURVE



KIT204096 - KIT PLINTH OUT

05

Installation procedure



Design and Installation


What to think about before?

- Countertop thickness
- Installation M1, M2, M3 (in terms of aesthetic profile position, protruding or perfectly aligned) on top or flush top
- Duct out or Recycling installation
- Power Supply and Electrical connections


LHOV

SUPER EASY INSTALLATION: 3 products in only 3 steps


① CONVEYOR



② OVEN




③ HOB



PRODUCT SUPPLY
OVEN - CONVEYOR ELECTRICAL
CONNECTION

HOB - OVEN ELECTRICAL
CONNECTION

Fitting supports



Thank you

elica

